FLIGHT SUMMARY REPORT

Flight Number: 97-009-02

Calendar/Julian Date: 14 September 1997 • 257

Sensor Package: Thermal Infrared Multispectral

Scanner (TIMS)

DoE Multispectral Scanner (MSS)

Area(s) Covered: Death Valley, Site 731

Mount Humphries, Site 750

Investigator(s): Gillespie, University of Washington Aircraft

Hook, JPL

Aircraft #: 799 Department of Energy Cessna Citation

SENSOR DATA

Accession #: ----

Sensor ID #: 086 1268

Sensor Type: TIMS MSS

Focal Length: ----

Film Type: ----

Filtration: ----

Spectral Band: ----

f Stop: -----

Shutter Speed: ----

of Frames: ----

Quality: Good Good

Remarks:

% Overlap:

Airborne Science and Applications Program

The Airborne Science Branch at NASA's Dryden Flight Research Center, Edwards, California, operates two ER-2 high altitude aircraft in support of NASA earth science research. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

Department of Energy Remote Sensing Laboratory

The NASA Airborne Science and Applications Program at Ames Research Center contracted with the Department of Energy Remote Sensing Laboratory (RSL) in Las Vegas, Nevada to fly the RSL Multispectral Scanner (MSS) and the NASA Thermal Infrared Multispectral Scanner (TIMS) over the desert southwest. The scanners were flown on the DOE Cessna Citation.

The Cessna Citation is a low and medium altitude, moderate speed aircraft. It can operate from 4,000 to 35,000 feet above sea level at speeds between 135 and 225 knots. There are two instrument ports in the aircraft. The RSL 1268 Multispectral Scanner was mounted over the aft port and the NASA Thermal Infrared Multispectral Scanner was mounted over the forward port.

RSL Daedalus 1268 MSS

The DOE Multispectral Scanner simulates the spectral characteristics the Thematic Mapper (TM) multispectral scanners orbiting on Landsat 4 and Landsat 5. The seven TM bands are replicated with the MSS and four additional bands of discrete wavelengths are acquired. THE MSS acquires TM band six (thermal data) as two bands in low and high gain settings. The scanner is configured as follows:

Daedalus Channel	TM Band	Wavelength, mm
1	A	0.42 - 0.45
2	1	0.45 - 0.52
3	2	0.52 - 0.60
4	В	0.60 - 0.62
5	3	0.63 - 0.69
6	C	0.69 - 0.75
7	4	0.75 - 0.90

8	D	0.91 - 1.05
9	5	1.55 - 1.75
10	7	2.08 - 2.35
11	6	8.5 - 12.5 low gain
12	6	8.5 - 12.5 high gain

Sensor/aircraft parameters are as follows:

IFOV: 2.5 mrad Total Scan Angle: 86° Pixels/Scan Line: 716

Scan Rate: 12.5/25/50/100 scans/second

Thermal Infrared Multispectral Scanner

The Thermal Infrared Multispectral Scanner (TIMS) is a multispectral scanning system using a dispersive grating and a six element mercury cadmium telluride detector array to produce six discrete channels in the 8.2 mm to 12.2 mm region.

<u>Channel</u>	Wavelength, mm	<u>NET</u>
1	8.2 - 8.6	< 0.30 C
2	8.6 - 9.0	< 0.30 C
3	9.0 - 9.4	< 0.30 C
4	9.4 - 10.2	< 0.30 C
5	10.2 - 11.2	< 0.30 C
6	11.2 - 12.2	$< 0.30 {\rm C}$

Sensor/aircraft parameters are as follows:

IFOV: 2.5 mrad

Ground Resolution: 163 feet (50 meters) at 65,000 feet

Total Scan Angle: 76.56°

Swath Width: 16.9 nmi (31.3 km) at 65,000 feet

Pixels/Scan Line: 638

Scan Rate: 7.3 (scans/second)
Ground Speed: 400 kts. (206 m/second)

Information on data tape format, logical record format, and scanner calibration data may be obtained from the Aircraft Data Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: 650-604-6252).

TIMS FLIGHT DATA FLIGHT NUMBER: 97-009-02

	Site	Line	Run	Act time begin	ual (GMT) end	Actu scanli begin e	ine	Alti feet/		Scan Speed (rps)	total G o o d scanlines	total Interpolated scanlines	total Repeated scanlines
1.	731	1	1	17:03:38.0	17:07:10.0	29094 3	34355	6000/	1829	25.00	5262	0	0
2.	731	1	2	17:10:48.0	17:14:51.0	39782 4	15841	6000/	1829	25.00	6060	0	0
3.	731	3	1	17:22:35.0	17:29:38.0	52409 6	52934	12000/	3658	25.00	10526	0	0
4.	731	2	1	17:34:34.0	17:38:42.0	70302 7	76457	12000/	3658	25.00	6156	0	0
5.	731	4	1	18:02:19.0	18:12:20.0	94647 10	9597	25000/	7620	25.00	14951	0	0
6.	750	2	1	18:36:21.0	18:37:39.0	145271 14	17214	25000/	7620	25.00	1944	0	0
7.	750	2	2	18:42:14.0	18:42:43.0	154060 15	54768	25000/	7620	25.00	709	0	0
8.	750	2	2	18:48:07.0	18:49:04.0	162824 16	54239	25000/	7620	25.00	1416	0	0
9.	750	1	1	18:58:39.0	19:00:41.0	178564 18	31580	6500/	1981	25.00	3017	0	0
10.	750	1	2	19:08:07.0	19:10:00.0	192692 19	95487	6500/	1981	25.00	2796	0	0

Note: Site 731 Death Valley Site 750 Mt Humphries

DOE DAEDALUS TMS FLIGHT DATA FLIGHT NUMBER: 97-009-02

	Site	Line	Run	Act time begin		Actual scanline begin end	Altitude feet/meter	Scan Speed (rps)	total G o o d scanlines	total Interpolated scanlines	total Repeated scanlines
1.	731	1	1	17:03:38.6	17:07:10.1	102347 107633	6000/ 1829	25.00	5287	0	0
2.	731	1	2	17:10:47.4	17:14:50.6	113065 119147	6000/ 1829	25.00	6083	0	0
3.	731	3	1	17:22:35.6	17:29:39.2	126787 132083	12000/ 3658	12.50	5297	0	0
4.	731	2	1	17:34:34.0	17:38:42.5	135768 138874	12000/ 3658	12.50	3107	0	0
5.	731	4	1	18:02:06.6	18:12:19.3	156425 164084	25000/ 7620	12.50	7660	0	0
6.	750	2	1	18:36:19.6	18:37:38.1	182088 183069	25000/ 7620	12.50	982	0	0
7.	750	2	2	18:42:13.1	18:42:42.1	186506 186869	25000/ 7620	12.50	364	0	0
8.	750	2	3	18:48:05.1	18:49:02.8	190906 191628	25000/ 7620	12.50	723	0	0
9.	750	1	1	18:58:39.9	19:00:44.3	205541 208650	6500/ 1981	25.00	3110	0	0
10.	750	1	2	19:08:06.7	19:09:59.0	219710 222518	6500/ 1981	25.00	2809	0	0

Note: Site 731 Death Valley Site 750 Mt Humphries





